
716F-NM



# Coaxial Adapter 7-16 female - N male

Coaxial Adapter, 7-16 Female/N Male



## **Technical Features**

SI			

Connector A

Dielectric

Product Line	Coaxial Cable Components	
Product Type	Coavial Adapter	

### **MECHANICAL SPECIFICATIONS**

Center Contact Connector A	Phosphor Bronze, silver plated
Outer Contact Connector A	Brass, Tri metal alloy plated
Connector B	N Male
Center Contact Connector B	Phosphor Bronze, silver plated
Outer Contact Connector B	Brass, Tri metal alloy plated

7-16 DIN Female

Silicone rubber

< -163

REV DATE: 18.Aug.2020

Gasket

Sealing class IP68, connected

### **ELECTRICAL SPECIFICATIONS**

Frequency Range	MHz	DC - 6000
VSWR, Return Loss	VSWR (dB)	0-2000 MHz: 1.04 (34.15) 2000-3000 MHz: 1.06 (30.71) 3000-6000 MHz: 1.10 (26.44)
Insertion Loss (Max)	dB	0.05

3rd Order IM Product @ 2x20 Watts
TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-40 to 85 (-40 to 185)
-----------------------	---------	------------------------

#### PACKAGING INFORMATION

716F-NM

Package Quantity

Evelous al	Dearmant	Links
Externa	Document	LINKS

**Notes** 

REV: C

www.rfsworld.com