


Coaxial Adapter N female - female

Coaxial Adapter N female - female



Technical Features

STRUCTURE			
Product Line		Coaxial Cable Components	
Product Type		Coaxial Adapter	
MECHANICAL SPECIFICATIONS			
Connector A		N Female	
Center Contact Connector A		Phosphor Bronze, silver plated	
Outer Contact Connector A		Brass, Tri metal alloy plated	
Connector B		N Female	
Center Contact Connector B		Phosphor Bronze, silver plated	
Outer Contact Connector B		Brass,Tri metal alloy plated	
Dielectric		PTFE	
Sealing class		IP68, connected	
ELECTRICAL SPECIFICATIONS			
Frequency Range	MHz	DC - 6000	
VSWR, Return Loss	VSWR (dB)	0-2000 MHz: 1.04 (34.15) 2000-3000 MHz: 1.06 (30.71) 3000-6000 MHz: 1.10 (26.44)	
Insertion Loss (Max)	dB	0.05	
3rd Order IM Product @ 2x20 Watts	dBc	< -163	
TEMPERATURE SPECIFICATIONS			
Operation Temperature	°C (°F)	-40 to 85 (-40 to 185)	
PACKAGING INFORMATION			
Package Quantity		1	

External Document Links Notes