


## Coaxial Adapter N male - female, right angle

Coaxial Adapter N male - female, right angle



### Technical Features

#### STRUCTURE

Product Line	Coaxial Cable Components
Product Type	Coaxial Adapter

#### MECHANICAL SPECIFICATIONS

Connector A	N Male
Center Contact Connector A	Brass, silver plated
Outer Contact Connector A	Brass, Tri metal alloy plated
Connector B	N Angle Female
Center Contact Connector B	Phosphor Bronze, silver plated
Outer Contact Connector B	Brass, Tri metal alloy plated
Dielectric	PTFE
Sealing class	IP68, connected

#### ELECTRICAL SPECIFICATIONS

Frequency Range	MHz	DC - 6000
VSWR, Return Loss	VSWR (dB)	0-2000 MHz: 1.05 (32.25) 2000 - 3000 MHz: 1.08 (28.3) 3000 - 6000 MHz: 1.12 (24.94)
Insertion Loss (Max)	dB	0.05
3rd Order IM Product @ 2x20 Watts	dBc	< -163

#### TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-40 to 85 (-40 to 185)
-----------------------	---------	------------------------

#### PACKAGING INFORMATION

Package Quantity	1
------------------	---

### External Document Links

### Notes