




IP65 Strong

1242x90x68mm




AC176-264V
 Package size of the lamp:
 1278x98x56mm
 PF ≥ 0,97



○ metal

Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70210-03000-6501840	18W	4000K	2100lm		
V1-I0-70210-03000-6501850	18W	5000K	2100lm		
V1-I0-70210-03000-6501865	18W	6500K	2200lm		
V1-I0-70210-03000-6503640	36W	4000K	4200lm		
V1-I0-70210-03000-6503650	36W	5000K	4200lm		
V1-I0-70210-03000-6503665	36W	6500K	4400lm		
V1-I0-70210-03000-6505440	54W	4000K	6300lm		
V1-I0-70210-03000-6505450	54W	5000K	6300lm		
V1-I0-70210-03000-6505465	54W	6500K	6600lm		



DC24-36V
 PF ≥ 0,97



○ metal

Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70210-03N00-6501840	18W	4000K	2100lm		
V1-I0-70210-03N00-6501850	18W	5000K	2100lm		
V1-I0-70210-03N00-6501865	18W	6500K	2200lm		
V1-I0-70210-03N00-6503640	36W	4000K	4200lm		
V1-I0-70210-03N00-6503650	36W	5000K	4200lm		
V1-I0-70210-03N00-6503665	36W	6500K	4400lm		



Diffuser (optional)

Pack size of the lens (3 pieces):
 1281x98x81mm

Diffuser (optional)

Pack size of the lens (3 pieces):
 688*98*81mm

Article	Type	Diffuser size
V2-I0-IPPO-02.3.0210.18	Clear	1242x90x68mm
V2-I0-IPMO-02.3.0210.18	Matt	1242x90x68mm

Article	Type	Diffuser size
V2-I0-IPPO-02.3.0215.18	Clear	674x90x68mm
V2-I0-IPMO-02.3.0215.18	Matt	674x90x68mm

*Luminous Flux Set excluding the diffuser

Installation:

Mount directly on a horizontal or vertical surface
 Can be mounted on hangers

Case:

High impact self-extinguishing ABS plastic
 It is completed with wearproof cable input

Diffuser:


Polycarbonate with UV stabilizer additives
 Mounted to the body of the lamp on the latches

Specifications:

Index of color transmission Ra > 80
 Temperature range from -40 °C to + 45 °C
 Network frequency 50Hz ± 10%
 LED life 50,000 hours
 3 year warranty
 Luminous flux Kn <1%




IP65 Strong
1242×90×68mm



DALI


AC176-264V
PF ≥ 0,97

Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70210-03D01-6503665	36W	3000K	4000lm		
V1-I0-70210-03D01-6503640	36W	4000K	4200lm		
V1-I0-70210-03D01-6503650	36W	5000K	4200lm		
V1-I0-70210-03D01-6503665	36W	6500K	4400lm		
V1-I0-70210-03D01-6505440	54W	4000K	6300lm		
V1-I0-70210-03D01-6505450	54W	5000K	6300lm		
V1-I0-70210-03D01-6505465	54W	6500K	6600lm		




SENSOR

AC176-264V
PF ≥ 0,97



Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70210-03S00-6501840	18W	4000K	2100lm		
V1-I0-70210-03S00-6501850	18W	5000K	2100lm		
V1-I0-70210-03S00-6501865	18W	6500K	2200lm		
V1-I0-70210-03S00-6503640	36W	4000K	4200lm		
V1-I0-70210-03S00-6503650	36W	5000K	4200lm		
V1-I0-70210-03S00-6503665	36W	6500K	4400lm		
V1-I0-70210-03S00-6505440	54W	4000K	6300lm		
V1-I0-70210-03S00-6505450	54W	5000K	6300lm		
V1-I0-70210-03S00-6505465	54W	6500K	6600lm		

IP65 Strong
1242×90×68mm



A

Autonomous emergency lamp constant action

Emergency power supply unit battery for 1 hour of autonomous operation, charge indicator, "Test" button in the set (see description on page 266)

Conformity:
Standard IEC 60598-2-22-2012 «Luminaires, Part 2-22. Private requirements. Luminaires for emergency lighting »
SP 52. 13330. 2011 "Natural and artificial lighting" (updated edition of SNiP 23.05-95)

Article	Power	Light temperature	Luminous flux*
V1-I0-70210-03A00-6501840	18W	4000K	2100lm
V1-I0-70210-03A00-6501850	18W	5000K	2100lm
V1-I0-70210-03A00-6501865	18W	6500K	2200lm
V1-I0-70210-03A00-6503640	36W	4000K	4200lm
V1-I0-70210-03A00-6503650	36W	5000K	4200lm
V1-I0-70210-03A00-6503665	36W	6500K	4400lm
V1-I0-70210-03A00-6505440	54W	4000K	6300lm
V1-I0-70210-03A00-6505450	54W	5000K	6300lm
V1-I0-70210-03A00-6505465	54W	6500K	6600lm

