

TUBI FLESSIBILI / FLEXIBLE HOSES



ATTACCO CONNECTION THREAD	Ø NOMINALE NOMINAL Ø	Ø TUBO INT./EST INLET/OUTLET Ø	PRESSIONE DI ESERCIZIO WORKING PRESSURE	LUNGHEZZA DISP. AVAILABLE LENGHT
1/2"	15	14x20	10	30 min/100 max
3/4"	18	19x26	10	30 min/100 max
1"	25	25x33	10	30 min/100 max
1" 1/4	32	32x42	6	30 min/100 max
1" 1/2	40	40x53	6	40 min/100 max
2"	50	50x65	6	40 min/100 max

Temperatura di funzionamento Working temperature - 5°C + 110°C

RACCORDI IN OTTONE / BRASS FITTINGS



TYPE	FILETTATURA THREAD	LUNGHEZZA LENGHT
RCM/F (2 ways)	1" M x 1" F	72 mm
RC3 (3 ways)	1" M x 1" F x 1" F	71 mm
RCC (5 ways)	1" M x 1" F x 1" F x 1/4" M x 1/4" F	72 mm
RCL (5 ways)	1" M x 1" F x 1" F x 1/4" M x 1/4" F	82 mm
RCLL (5 ways)	1" M x 1" F x 1" F x 1/4" M x 1/4" F	91 mm
ROMF1-3	diritto in 3 pz 1" MF con o-ring 3 pieces straight fitting MF 1" with o-ring	
ROMF114-3	diritto in 3 pz 1" 1/4 MF con o-ring 3 pieces straight fitting MF 1" 1/4 with o-ring	
ROMFC114-3-03	curvo in 3 pz 1" 1/4 con o-ring 3 pieces elbow MF 1" 1/4 with o-ring	

VALVOLE DI SICUREZZA / SAFETY VALVES



VS

TYPE	FILETTATURA THREAD
NT1: 0,5÷5 bar – NT2: 6÷12 bar – NT3: 13÷18 bar	1/8" – 1/4" – 3/8" – 1/2" – 3/4" – 1"

Temperatura di esercizio Working temperature NBR - 10°C + 90°C / VITON -10°C + 250°C

su richiesta on request PED 97/23/CE
PED 97/23CE versione pre-tarata
PED 97/23CE calibrated version

anello di ispezione inspection ring

uso: use: aria compressa compressed air

VALVOLE DI RITEGNO E DI FONDO IN OTTONE / BRASS CHECK VALVES AND FOOT VALVES



TYPE	FILETTATURA THREAD	PRESSIONE MAX. D'ESERCIZIO MAX. WORKING PRESSURE
Valvola di ritegno universale F/F (VARY) Standard check valve F/F (VARY)	1/4" – 3/8" – 1/2" – 3/4" – 1"	12 bar
	1" 1/4 – 1" 1/2 – 2"	10 bar
	2" 1/2 – 3" – 4"	8 bar
Valvola di ritegno universale FF per pressioni elevate (VARE) Standard check valve FF for high pressure (VARE)	3/8" – 1/2" – 3/4" – 1"	25 bar
	1" 1/4 – 1" 1/2 – 2"	18 bar
	2" 1/2 – 3" – 4"	12 bar
Valvola di fondo con filtro in acciaio inox incorporato (VAFY) Foot valve with embodied stainless steel filter (VAFY)	3/8" – 1/2" – 3/4" – 1"	10 bar
	1" 1/4 – 1" 1/2 – 2"	8 bar
	2" 1/2 – 3" – 4"	6 bar
Valvola di fondo con filtro in acciaio inox (VAFE) Foot valve with stainless steel filter (VAFE)	3/8" – 1/2" – 3/4" – 1"	25 bar
	1" 1/4 – 1" 1/2 – 2"	18 bar
	2" 1/2 – 3" – 4"	12 bar