## HYDRA SELF-CLEANING FILTERS

#### **Housings HYDRA fit to EXCLUSIVE** HYDRA FILTER CARTRIDGES.

cartridges with antimicrobial flat seal.



# stainless steel

net cartridge, filtration at 90 micron. CODE RA5000020



**RAH** HOT

stainless steel net cartridge, filtration at 90 micron. CODE RA5080020



plastic net cartridge, filtration at 90 micron. CODE RA5000010



pleated plastic net cartridge,

filtration at 50 micron. CODE RA5000040



All cartridges are provided with dedicated stainless steel **AISI 302** cartridge spring.


CODE RE7120040

RSH

RLH

#### FLOW RATE VS PRESSURE DROP Ap

Testing mode: 20°C, 3 BAR







A range of housings is certified by IAPMO RT to NSF/ANSI 42, 61, 372 - lead free, CSA B483.1. In compliance with Drinking Water Treatment Units regulations, USA and CANADA.









Housings are tested and certified under the most stringent procedures worldwide, in compliance with DM 25 (Italy), with the sanitary certification ACS (France), EAC/Ghostreghistrazia (Russia) and WaterMark (Australia).

#### SYMBOLS LEGEND



For domestic use



For technical and industrial use



Filter housings made in PET, a highly recyclable plastic, are manufactured with a proprietary procedure saving up to 60% of energy in injection molding

compared with standard plastics. That is one of Atlas Filtri commitments to comply with Kyoto Treaty for the reduction of green house gas (CO<sub>2</sub>) emissions in the atmosphere.

#### ACCESSORIES ON DEMAND





CODE RE7120026

brass hose-holder 3/4"/ 1" brass nipples with o-ring (pair) CODE RB7404001 / CODE RB7404002







-KIT AUTO- CODE RE7120024 automatic discharge kit (see pages 186-187)



-LUBRIKIT- single-dose lubricant for housing o-ring CODE RE9020650





-X- spanner

-S- wall bracket (for HYDRA and HYDRA HOT)



-K DP- wall bracket (for HYDRA K DP) CODE RB7400021

#### DISCHARGE KIT



brass discharge ball-valve with gasket



plastic hose-holder



drain funnel

In compliance with the European Standard UNI EN 1717/2002: designed to prevent back-flow contamination by making all elements downstream the discharge vent to atmosphere (protection unit symbol: DC)

#### HOUSINGS RANGE







\* BSP parallel (cylindrical) ISO 228

FILTER MODEL




1"1/2

\* NPT tapered (conical) ANSI/ASME B1.20.1 Self-Cleaning Filters















WORKING CONDITIONS	
Max working pressure:	
BSP versions	8 bar (116 psi)
NPT versions	8,6 bar (125 psi)
Min working pressure	1,8 bar (26 psi)
Max working temperature	45°C (113°F)
Min working temperature _	4°C (39,2°F)



#### SPECIFICATIONS

Non-toxic materials, suitable for drinking water. Head: reinforced polypropylene.

Bowl: PET.
O-ring: EPDM.
Breather-valve: body stainless steel, o-ring EPDM.
IN/OUT brass threads: CW 617 N brass.
Discharge ball-valve: CW 617 N brass nickel plated.

Drain funnel: reinforced polypropylene.

### HYDRA RLH single-stage self-cleaning filters

HOUSINGS WITH BRASS BSP THREADS									
CODE	MODEL	NOMINAL	IN/OUT	FLOW	DIMENSIONS r		mm		
		FILTRATION MICRON		RATE I/h	Α	В	С		
RA6000010	HYDRA 1/2" RLH 90 mcr OT	90	1/2"	3500	390	120	107		
RA6000011	HYDRA 3/4" RLH 90 mcr OT	90	3/4"	5000	390	120	107		
RA6000012	HYDRA 1" RLH 90 mcr OT	90	1"	6000	390	120	107		
RA6000022	HYDRA 1"1/4 RLH 90 mcr OT	90	1"1/4	8000	415	120	107		
RA6000023	HYDRA 1"1/2 RLH 90 mcr OT	90	1"1/2	10000	415	120	107		

HOUSINGS W	ITH PLASTIC BSP THREADS						
CODE	MODEL	NOMINAL	IN/OUT	FLOW	DIM	ENSIONS	mm
		FILTRATION MICRON		RATE I/h	Α	В	С
RA6000028	HYDRA 1/2" RLH 90 mcr IN	90	1/2"	3500	390	120	107
RA6000029	HYDRA 3/4" RLH 90 mcr IN	90	3/4"	5000	390	120	107
RA6000030	HYDRA 1" RLH 90 mcr IN	90	1"	6000	390	120	107

HOUSINGS WITH PLASTIC NPT THREADS									
CODE	MODEL	NOMINAL	IN/OUT	FLOW	DIMENSIONS m		mm		
		FILTRATION MICRON		RATE I/h	Α	В	С		
RA6000053	HYDRA 1/2" RLH 90 mcr NPT IN	90	1/2"	5000	390	120	107		
RA6000033	HYDRA 3/4" RLH 90 mcr NPT IN	90	3/4"	5000	390	120	107		
RA6000034	HYDRA 1" RLH 90 mcr NPT IN	90	1"	6000	390	120	107		

HOUSINGS WITH PLASTIC BSP THREADS									
CODE	MODEL	NOMINAL	IN/OUT	FLOW	DIMENSIONS m		mm		
		FILTRATION MICRON		RATE I/h	Α	В	С		
RA6000060	HYDRA 1/2" RLH 90 mcr MP	90	1/2"	3500	390	155	107		
RA6000061	HYDRA 3/4" RLH 90 mcr MP	90	3/4"	5000	390	155	107		
RA6000062	HYDRA 1" RLH 90 mcr MP	90	1"	6000	390	155	107		