


NEW
MODEL



Strong 2.0

1242×90×68mm




AC176-264V
Package size of the lamp:
1278×98×56mm
Kn<2%
PF ≥ 0,95
Ra>84



○ metallic

Article	Power	Light temperature	Light flow	Diffuser	Clear diffuser
V1-I2-70210-03G02-6503065	30W	6500K	3600lm	Matt	
V1-I2-70210-03G02-6504565	45W	6500K	5400lm	Matt	
V1-I2-70210-03G00-6503065	30W	6500K	3900lm	Clear	
V1-I2-70210-03G00-6504565	45W	6500K	5850lm	Clear	
V1-I2-70210-03G02-6503050	30W	5000K	3600lm	Matt	
V1-I2-70210-03G02-6504550	45W	5000K	5400lm	Matt	
V1-I2-70210-03G00-6503050	30W	5000K	3900lm	Clear	
V1-I2-70210-03G00-6504550	45W	5000K	5850lm	Clear	
V1-I2-70210-03G02-6503040	30W	4000K	3600lm	Matt	
V1-I2-70210-03G02-6504540	45W	4000K	5400lm	Matt	
V1-I2-70210-03G00-6503040	30W	4000K	3900lm	Clear	
V1-I2-70210-03G00-6504540	45W	4000K	5850lm	Clear	
V1-I2-70210-03G02-6503030	30W	3000K	3240lm	Matt	
V1-I2-70210-03G02-6504530	45W	3000K	4860lm	Matt	
V1-I2-70210-03G00-6503030	30W	3000K	3510lm	Clear	
V1-I2-70210-03G00-6504530	45W	3000K	5265lm	Clear	



DC24-36V
PF ≥ 0,97



○ metallic

Article	Power	Light temperature	Light flow	Diffuser	Clear diffuser
V1-I2-70210-03N02-6503065	30W	6500K	3600lm	Matt	
V1-I2-70210-03N02-6504565	45W	6500K	5400lm	Matt	
V1-I2-70210-03N00-6503065	30W	6500K	3900lm	Clear	
V1-I2-70210-03N00-6504565	45W	6500K	5850lm	Clear	
V1-I2-70210-03N02-6503050	30W	5000K	3600lm	Matt	
V1-I2-70210-03N02-6504550	45W	5000K	5400lm	Matt	
V1-I2-70210-03N00-6503050	30W	5000K	3900lm	Clear	
V1-I2-70210-03N00-6504550	45W	5000K	5850lm	Clear	
V1-I2-70210-03N02-6503040	30W	4000K	3600lm	Matt	
V1-I2-70210-03N02-6504540	45W	4000K	5400lm	Matt	
V1-I2-70210-03N00-6503040	30W	4000K	3900lm	Clear	
V1-I2-70210-03N00-6504540	45W	4000K	5850lm	Clear	
V1-I2-70210-03N02-6503030	30W	3000K	3240lm	Matt	
V1-I2-70210-03N02-6504530	45W	3000K	4860lm	Matt	
V1-I2-70210-03N00-6503030	30W	3000K	3510lm	Clear	
V1-I2-70210-03N00-6504530	45W	3000K	5265lm	Clear	

Installation:

Mount directly on a horizontal or vertical surface
Can be mounted on hangers

Case:

High impact self-extinguishing ABS plastic
It is completed with wearproof cable input

Diffuser:


Polycarbonate with UV stabilizer additives
Mounted to the body of the lamp on the latches

Specifications:

Index of color transmission Ra > 80
Temperature range from -40 °C to + 45 °C
Network frequency 50Hz ± 10%
LED life 50,000 hours
3 year warranty
Luminous flux Kn <1%



Strong 2.0
1242×90×68mm




DALI

AC176-264V
PF ≥ 0,97

Article	Power	Light temperature	Light flow	Diffuser	Matt Diffuser	Clear Diffuser
V1-I2-70210-03D02-6503065	30W	6500K	3600lm	Matt		
V1-I2-70210-03D02-6504565	45W	6500K	5400lm	Matt		
V1-I2-70210-03D00-6503065	30W	6500K	3900lm	Clear		
V1-I2-70210-03D00-6504565	45W	6500K	5850lm	Clear		
V1-I2-70210-03D02-6503050	30W	5000K	3600lm	Matt		
V1-I2-70210-03D02-6504550	45W	5000K	5400lm	Matt		
V1-I2-70210-03D00-6503050	30W	5000K	3900lm	Clear		
V1-I2-70210-03D00-6504550	45W	5000K	5850lm	Clear		
V1-I2-70210-03D02-6503040	30W	4000K	3600lm	Matt		
V1-I2-70210-03D02-6504540	45W	4000K	5400lm	Matt		
V1-I2-70210-03D00-6503040	30W	4000K	3900lm	Clear		
V1-I2-70210-03D00-6504540	45W	4000K	5850lm	Clear		
V1-I2-70210-03D02-6503030	30W	3000K	3240lm	Matt		
V1-I2-70210-03D02-6504530	45W	3000K	4860lm	Matt		
V1-I2-70210-03D00-6503030	30W	3000K	3510lm	Clear		
V1-I2-70210-03D00-6504530	45W	3000K	5265lm	Clear		

Strong 2.0
1242×90×68mm




Autonomous emergency lamp constant action

Emergency power supply unit, battery for 1 hour of autonomous operation, charge indicator, "Test" button in the set (see description on page 266)


Conformity:

Standard IEC 60598-2-22:2012 "Luminaires. Part 2-22. Private requirements. Luminaires for emergency lighting" SP 52. 13330. 2011 "Natural and artificial lighting" (updated edition of SNiP 23.05-95)

Article	Power	Light temperature	Light flow	Diffuser
V1-I2-70210-03A02-6503065	30W	6500K	3600lm	Matt
V1-I2-70210-03A02-6504565	45W	6500K	5400lm	Matt
V1-I2-70210-03A00-6503065	30W	6500K	3900lm	Clear
V1-I2-70210-03A00-6504565	45W	6500K	5850lm	Clear
V1-I2-70210-03A02-6503050	30W	5000K	3600lm	Matt
V1-I2-70210-03A02-6504550	45W	5000K	5400lm	Matt
V1-I2-70210-03A00-6503050	30W	5000K	3900lm	Clear
V1-I2-70210-03A00-6504550	45W	5000K	5850lm	Clear
V1-I2-70210-03A02-6503040	30W	4000K	3600lm	Matt
V1-I2-70210-03A02-6504540	45W	4000K	5400lm	Matt
V1-I2-70210-03A00-6503040	30W	4000K	3900lm	Clear
V1-I2-70210-03A00-6504540	45W	4000K	5850lm	Clear
V1-I2-70210-03A02-6503030	30W	3000K	3240lm	Matt
V1-I2-70210-03A02-6504530	45W	3000K	4860lm	Matt
V1-I2-70210-03A00-6503030	30W	3000K	3510lm	Clear
V1-I2-70210-03A00-6504530	45W	3000K	5265lm	Clear



AC176-264V
PF ≥ 0,97



Article	Power	Light temperature	Light flow	Diffuser	Matt Diffuser	Clear Diffuser
V1-I2-70210-03S02-6503065	30W	6500K	3600lm	Matt		
V1-I2-70210-03S02-6504565	45W	6500K	5400lm	Matt		
V1-I2-70210-03S00-6503065	30W	6500K	3900lm	Clear		
V1-I2-70210-03S00-6504565	45W	6500K	5850lm	Clear		
V1-I2-70210-03S02-6503050	30W	5000K	3600lm	Matt		
V1-I2-70210-03S02-6504550	45W	5000K	5400lm	Matt		
V1-I2-70210-03S00-6503050	30W	5000K	3900lm	Clear		
V1-I2-70210-03S00-6504550	45W	5000K	5850lm	Clear		
V1-I2-70210-03S02-6503040	30W	4000K	3600lm	Matt		
V1-I2-70210-03S02-6504540	45W	4000K	5400lm	Matt		
V1-I2-70210-03S00-6503040	30W	4000K	3900lm	Clear		
V1-I2-70210-03S00-6504540	45W	4000K	5850lm	Clear		
V1-I2-70210-03S02-6503030	30W	3000K	3240lm	Matt		
V1-I2-70210-03S02-6504530	45W	3000K	4860lm	Matt		
V1-I2-70210-03S00-6503030	30W	3000K	3510lm	Clear		
V1-I2-70210-03S00-6504530	45W	3000K	5265lm	Clear		

